

Kantholz / Dielen / Latten / Schalung/ Rauspund

Kantholz / Dielen, A/B GK II

Fi/Ta/Ki impr., frisch

Dimension in cm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
4 x 16 cm			X	X			
4 x 20 cm			X	X	X		
5 x 10 cm				X			
5 x 20 cm				X	X		
5 x 25 cm				X			
6 x 8 cm			X	X			
6 x 12 cm			X	X	X		
6 x 16 cm			X	X	X		
6 x 20 cm				X	X		
8 x 8 cm				X			
8 x 16 cm			X	X	X		
8 x 18 cm					X		
8 x 20 cm				X	X		X (A)
10 x 10 cm		X	X	X	X		
12 x 12 cm			X	X	X		
12 x 16 cm					X		
12 x 20 cm					X		
14 x 14 cm			X	X	X		
16 x 16 cm			X	X	X		
20 x 20 cm					X		X
20 x 24 cm				X			X

Latten

Fi/Ta/Ki impr., frisch

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
24 x 48 mm	X		X				
28 x 48 mm			X				
38 x 58 mm		X	X	X	X		

Alle Längen mit (A) gekennzeichnet sind Auslaufartikel

Dachlatten S10, DIN 4074

Fi/Ta/Ki impr., frisch

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
30 x 50 mm				x			
40 x 60 mm				x			

Schalung

Fi/Ta/Ki impr., frisch

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
24 x 80 mm			x	x			
24 x 100 mm		x	x	x			
24 x 160 mm		x	x	x			

Rauspund

Fi/Ta/Ki impr., frisch

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
21 x 116 mm			x				
24 x 116 mm			x	x			

Kantholz / Dielen, A/B GK II

Fi/Ta/Ki, roh, frisch

Dimension in cm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
4 x 20 cm			x				
10 x 10 cm			x				

Dielen

scharfkantig, GK I-III

Fi/Ta/Ki, HRF 18-20 %, trocken

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
39 x 200 mm				x			

Keilbohlen

Fi/Ta/Ki, HRF 18-20 % trocken

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
0:62 x 185 mm				x			

Latten

Fi/Ta/Ki, HRF 18-20 %, trocken

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
24 x 48 mm	x						

Dachlatten CE, S10, DIN 4074-1

Fi/Ta/Ki, HRF 18-20 %, trocken

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
30 x 50 mm				x			
40 x 60 mm				x			

Schalung

Fi/Ta/Ki, HRF 18-20 %, trocken

Dimension in mm	Längen in m						
	1,35 m	3,00 m	4,00 m	5,00 m	6,00 m	7,00 m	8,00 m
23 x 100 mm			x				

Rauspund, Keil-Nut+Feder

nord. Fichte, HRF 18-20 %, trocken

Dimension in mm	Längen in m						
	21,0 x 121 mm	nach Lagervorrat					
24,0 x 121 mm							
28,5 x 146 mm							
35,0 x 146 mm							